

ROHS COMPLIANT

PRODUCT DATA DRAWING

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	NRN 42975	03/19	GPF
A	DCN 48594	05/23	GPF
B	DCN 49803	05/20	STW

MATERIAL:

CONNECTORS:

CABLE:

SHRINK TUBING:

PERFORMANCE:

IMPEDANCE:

FREQ. RANGE:

2.4MM PLUG (SF1611-60003)

SMPM JACK (3221-40006)

T-FLEX 405

M23053/5

50 OHMS

DC TO 40.0 GHz

SV P/N		OAL	
7016-0070		6.000	
7016-0071		12.000	

MATERIAL:	SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES:	UNLESS OTHERWISE SPECIFIED 1) ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63-MIL-STD-10. 6) DIA.'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 7) REMOVE ALL BURRS	<div>Amphenol SV MICROWAVE www.svmicrowave.com</div> <div>TITLE: 2.4mm PLUG TO SMPM JACK FOR .085 T-FLEX 405 CABLE ASSEMBLY</div>	
FINISH:	SEE NOTES	FRACTIONAL: ±1/64 ANGULAR: X° ±1°0' X°X' ±15'			
SURFACE AREA:	N/A	DECIMAL: .X ±.030 .XX ±.010 .XXX ±.005			
PROPRIETARY THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.		INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994		SIZE DWG. NO. B 7016-0070-0071	
		THIRD ANGLE PROJECTION	DRAWN: SJ 03/29/19	SCALE: 2:1	
			CHECKED: GPF 03/29/19	SHEET 1 OF 1	
			APPROVED: GPF 03/29/19		